

Photo Cotton Rag 315gsm IFA 11

Product Description

Ultra -smooth 100% cotton, matte finish, fourdrinier made digital fine art paper. Instant dry, aqueous pigment and dye inkjet compatible with excellent colour gamut and exceptional d-max.

Free From Optical Brighteners



Features

- ✓ Ultra-Smooth Surface
- ✓ 100% Cotton Rag
- ✓ Natural White
- ✓ OBA Free
- ✓ Acid - Lignin Free - Archival

Applications

- Fine Art and Photographic Open and Limited Edition Prints
- Fine Art and Fine Photographic Reproduction and Restoration
- Art and Photo Portfolios
- Photo Albums, Memory Books and Wedding Albums
- Greeting Cards and Postcards

Basic Weight (gsm)	315		
Paper Thickness (Microns)	310	Paper Thickness (Inches)	0.012
Base Material	100% Cotton		
Coating Type	Matte		
Surface Texture	Ultra-Smooth		
Whiteness (CIE)	109		
Brightness (TAPPI)	99		
OBA Content	No		
pH	7.5-9.5		
Recyclable	Yes		
Print Settings*	MK Ink, Enhanced Matte or Fine Art Paper Settings are recommended as a starting point		
Notes			

*Generic ICC Profiles for selected printer models are available from the Innova Art website.

Sheets	A4, A3, A3+, A2, 8.5x11", 13x19", 17x22", 36x48"
Rolls (15m/50ft Length)	17", 24", 36", 44", 60"

Additional Sizes are available on request, subject to order quantity.

Handling and Storage

- All digital Fine Art Papers and Canvases are fragile and need to be handled with extreme care. Try not to touch the surface of the paper, always hold the paper by the edges and wear cotton gloves if necessary.
- Return unused material to the original box and only store finished prints in archival quality packaging. If mounting or framing, use only archive grade tapes and glues.
- After printing, leave prints open to the air to fully dry (24 hours is recommended). Do not stack prints on top of each other straight away.
- Using a giclée varnish or spray will help protect your print from damage, effects of UV light and environmental attack.

Conditions of Use

- The recommended climate for storage of all papers is 15-20°C, relative humidity of 40-60%. Always store in original packaging, out of direct sunlight and protected from moisture.
- Do not exceed temperatures of 82°C (180°F) when dry mounting.

All recommendations are for your guidance only. These are subject to our test criteria, which remain subject to change without prior notice.

Fabiano Printmaking Rag 310gsm IFA 107

Product Description

Soft grain 100% cotton, matte finish, mould made digital fine art paper. Aqueous pigment and dye inkjet compatible with excellent colour gamut and exceptional d-max.

Free From Optical Brighteners



Features

- ✓ Soft Grain – Mould Made
- ✓ 100% Cotton Rag
- ✓ Natural White
- ✓ OBA Free
- ✓ Acid - Lignin Free - Archival

Applications

- Fine Art and Photographic Open and Limited Edition Prints
- Fine Art and Fine Photographic Reproduction and Restoration
- Art and Photo Portfolios

Basic Weight (gsm)	310		
Paper Thickness (Microns)	565	Paper Thickness (Inches)	0.022
Base Material	100% Cotton		
Coating Type	Matte		
Surface Texture	Soft Grain 'Etching'		
Whiteness (CIE)	86		
Brightness (TAPPI)	97.3		
OBA Content	No		
pH	7.5		
Recyclable	Yes		
Print Settings*	MK Ink, a Textured Fine Art Paper setting is recommended as a starting point		
Notes			

*Generic ICC Profiles for selected printer models are available from the Innova Art website.

Sheets	A4, A3, A3+, A2, 8.5x11", 13x19", 17x22", 36x48"
Rolls (15m/50ft Length)	17", 24", 36", 44", 60"

Additional Sizes are available on request, subject to order quantity.

Handling and Storage

- All digital Fine Art Papers and Canvases are fragile and need to be handled with extreme care. Try not to touch the surface of the paper, always hold the paper by the edges and wear cotton gloves if necessary.
- Return unused material to the original box and only store finished prints in archival quality packaging. If mounting or framing, use only archive grade tapes and glues.
- After printing, leave prints open to the air to fully dry (24 hours is recommended). Do not stack prints on top of each other straight away.
- Using a giclée varnish or spray will help protect your print from damage, effects of UV light and environmental attack.

Conditions of Use

- The recommended climate for storage of all papers is 15-20°C, relative humidity of 40-60%. Always store in original packaging, out of direct sunlight and protected from moisture.
- Do not exceed temperatures of 82°C (180°F) when dry mounting.

All recommendations are for your guidance only. These are subject to our test criteria, which remain subject to change without prior notice.

Etching Cotton Rag 315gsm IFA 22

Product Description

Soft grain 100% cotton, matte finish, fourdriner made digital fine art paper. Instant dry, aqueous pigment and dye inkjet compatible with excellent colour gamut and exceptional d-max.

Free From Optical Brighteners



Features

- ✓ Soft Grain Etching
- ✓ 100% Cotton Rag
- ✓ Natural White
- ✓ OBA Free
- ✓ Acid - Lignin Free - Archival

Applications

- Fine Art and Photographic Open and Limited Edition Prints
- Fine Art and Fine Photographic Reproduction and Restoration
- Art and Photo Portfolios
- Photo Albums, Memory Books and Wedding Albums
- Greeting Cards and Postcards

Basic Weight (gsm)	315		
Paper Thickness (Microns)	460	Paper Thickness (Inches)	0.018
Base Material	100% Cotton		
Coating Type	Matte		
Surface Texture	Soft Grain 'Etching'		
Whiteness (CIE)	109		
Brightness (TAPPI)	86		
OBA Content	No		
pH	7.5-9.5		
Recyclable	Yes		
Print Settings*	MK Ink, Fine Art Textured or Archival Matte Paper Settings are recommended as a starting point		
Notes			

*Generic ICC Profiles for selected printer models are available from the Innova Art website.

Sheets	A4, A3, A3+, A2, 8.5x11", 13x19", 17x22", 36x48"
Rolls (15m/50ft Length)	17", 24", 36", 44", 60"

Additional Sizes are available on request, subject to order quantity.

Handling and Storage

- All digital Fine Art Papers and Canvases are fragile and need to be handled with extreme care. Try not to touch the surface of the paper, always hold the paper by the edges and wear cotton gloves if necessary.
- Return unused material to the original box and only store finished prints in archival quality packaging. If mounting or framing, use only archive grade tapes and glues.
- After printing, leave prints open to the air to fully dry (24 hours is recommended). Do not stack prints on top of each other straight away.
- Using a giclée varnish or spray will help protect your print from damage, effects of UV light and environmental attack.

Conditions of Use

- The recommended climate for storage of all papers is 15-20°C, relative humidity of 40-60%. Always store in original packaging, out of direct sunlight and protected from moisture.
- Do not exceed temperatures of 82°C (180°F) when dry mounting.

All recommendations are for your guidance only. These are subject to our test criteria, which remain subject to change without prior notice.

Fabiano Artístico Watercolour Rag 310gsm IFA 108

Product Description

Fabiano Artístico Watercolour 100% cotton, matte finish, mould made digital fine art paper. Aqueous pigment and dye inkjet compatible with excellent colour gamut and exceptional d-max.

Free From Optical Brighteners



Features

- ✓ Artístico Watercolour – Mould Made
- ✓ 100% Cotton Rag
- ✓ Natural White
- ✓ OBA Free
- ✓ Acid - Lignin Free - Archival

Applications

- Fine Art and Photographic Open and Limited Edition Prints
- Fine Art and Fine Photographic Reproduction and Restoration
- Art and Photo Exhibitions

Basic Weight (gsm)	310		
Paper Thickness (Microns)	565	Paper Thickness (Inches)	0.022
Base Material	100% Cotton		
Coating Type	Matte		
Surface Texture	Rough 'Watercolour'		
Whiteness (CIE)	86		
Brightness (TAPPI)	97.3		
OBA Content	No		
pH	7.5		
Recyclable	Yes		
Print Settings*	MK Ink, a Textured Fine Art Paper setting is recommended as a starting point		
Notes			

*Generic ICC Profiles for selected printer models are available from the Innova Art website.

Sheets	A4, A3, A3+, A2, 8.5x11", 13x19", 17x22", 36x48"
Rolls (15m/50ft Length)	17", 24", 36", 44", 60"

Additional Sizes are available on request, subject to order quantity.

Handling and Storage

- All digital Fine Art Papers and Canvases are fragile and need to be handled with extreme care. Try not to touch the surface of the paper, always hold the paper by the edges and wear cotton gloves if necessary.
- Return unused material to the original box and only store finished prints in archival quality packaging. If mounting or framing, use only archive grade tapes and glues.
- After printing, leave prints open to the air to fully dry (24 hours is recommended). Do not stack prints on top of each other straight away.
- Using a giclée varnish or spray will help protect your print from damage, effects of UV light and environmental attack.

Conditions of Use

- The recommended climate for storage of all papers is 15-20°C, relative humidity of 40-60%. Always store in original packaging, out of direct sunlight and protected from moisture.
- Do not exceed temperatures of 82°C (180°F) when dry mounting.

All recommendations are for your guidance only. These are subject to our test criteria, which remain subject to change without prior notice.

Exhibition Cotton Gloss 335gsm IFA 45

Product Description

Smooth 100% cotton, gloss finish, fourdriner made digital fine art paper. Instant dry, aqueous pigment and dye inkjet compatible with excellent colour gamut and exceptional d-max.

Free From Optical Brighteners



Features

- ✓ Smooth Gloss
- ✓ 100% Cotton
- ✓ Natural White
- ✓ OBA Free
- ✓ Acid - Lignin Free – Archival
- ✓ Crystal Layer Coating Technology

Applications

- Fine Art and Photographic Open and Limited Edition Prints
- Fine Art and Fine Photographic Reproduction and Restoration
- Art and Photo Portfolios
- Photo Albums, Memory Books and Wedding Albums
- Greeting Cards and Postcards

Basic Weight (gsm)	335		
Paper Thickness (Microns)	390	Paper Thickness (Inches)	0.015
Base Material	100% Cotton		
Coating Type	Microporous Gloss		
Surface Texture	Smooth		
Whiteness (CIE)	75		
Brightness (TAPPI)	85		
OBA Content	None		
pH	7.5-9.5		
Recyclable	Yes		
Print Settings*	PK Ink, Semi Gloss or Lustre Photo Paper settings are recommended as a starting point		
Notes	Glossy papers mark more easily, it is recommended to wear cotton gloves when handling. Crystal Layer technology creates a barrier between the fibre base and the microporous glossy coating allowing the paper to maintain excellent sharp detail and an enhanced tonal range.		

*Generic ICC Profiles for selected printer models are available from the Innova Art website.

Sheets	A4, A3, A3+, A2, 8.5x11", 13x19", 17x22"
Rolls (15m/50ft Length)	17", 24", 36", 44", 60"

Additional Sizes are available on request, subject to order quantity.

Handling and Storage

- All digital Fine Art Papers and Canvases are fragile and need to be handled with extreme care. Try not to touch the surface of the paper, always hold the paper by the edges and wear cotton gloves if necessary.
- Return unused material to the original box and only store finished prints in archival quality packaging. If mounting or framing, use only archive grade tapes and glues.
- After printing, leave prints open to the air to fully dry (24 hours is recommended). Do not stack prints on top of each other straight away.
- Using a giclée varnish or spray will help protect your print from damage, effects of UV light and environmental attack.

Conditions of Use

- The recommended climate for storage of all papers is 15-20°C, relative humidity of 40-60%. Always store in original packaging, out of direct sunlight and protected from moisture.
- Do not exceed temperatures of 82°C (180°F) when dry mounting.

All recommendations are for your guidance only. These are subject to our test criteria, which remain subject to change without prior notice.

Exhibition Photo Baryta 310gsm IFA 69

Product Description

Smooth baryta alpha cellulose base, gloss finish, fourdrinier made digital fine art paper. Instant dry, aqueous pigment and dye inkjet compatible with excellent colour gamut and exceptional d-max.

True Barium Sulphate Layer



Features

- ✓ Ultra-Smooth Gloss
- ✓ Alpha Cellulose
- ✓ High White
- ✓ Acid - Lignin Free – Archival
- ✓ Crystal Layer Coating Technology

Applications

- Fine Art and Photographic Open and Limited Edition Prints
- Fine Art and Fine Photographic Reproduction and Restoration
- Art and Photo Portfolios or Albums, Memory Books or Wedding Albums
- Black and White Archival Prints

Basic Weight (gsm)	310		
Paper Thickness (Microns)	315	Paper Thickness (Inches)	0.012
Base Material	Alpha Cellulose		
Coating Type	Microporous Silk		
Surface Texture	Ultra Smooth		
Whiteness (CIE)	100		
Brightness (TAPPI)	96		
OBA Content	No		
pH	7.5-9.5		
Recyclable	Yes		
Print Settings*	PK Ink, Semi Gloss or Lustre Photo Paper Settings are recommended as a starting point		
Notes	Glossy papers mark more easily, it is recommended to wear cotton gloves when handling. Crystal Layer technology creates a barrier between the fibre base and the microporous glossy coating allowing the paper to maintain excellent sharp detail and an enhanced tonal range.		

*Generic ICC Profiles for selected printer models are available from the Innova Art website.

Sheets	A4, A3, A3+, A2, 8.5x11", 13x19", 17x22"
Rolls (15m/50ft Length)	17", 24", 36", 44", 50"

Additional Sizes are available on request, subject to order quantity.

Handling and Storage

- All digital Fine Art Papers and Canvases are fragile and need to be handled with extreme care. Try not to touch the surface of the paper, always hold the paper by the edges and wear cotton gloves if necessary.
- Return unused material to the original box and only store finished prints in archival quality packaging. If mounting or framing, use only archive grade tapes and glues.
- After printing, leave prints open to the air to fully dry (24 hours is recommended). Do not stack prints on top of each other straight away.
- Using a giclée varnish or spray will help protect your print from damage, effects of UV light and environmental attack.

Conditions of Use

- The recommended climate for storage of all papers is 15-20°C, relative humidity of 40-60%. Always store in original packaging, out of direct sunlight and protected from moisture.
- Do not exceed temperatures of 82°C (180°F) when dry mounting.

All recommendations are for your guidance only. These are subject to our test criteria, which remain subject to change without prior notice.